

KIMICAR SRL
27040 Bosnasco (Pavia) Italy - Via Fabbrica, 1/C
Tel. (39) 0385 272.247 - Fax (39) 0385 272.240
<http://www.kimicar.it> - e mail: info@kimicar.it

Cap. Soc. € 46.800,00 i.v. – Cod. Fisc. e P. IVA 01790620189
N° Iscr. Registro Imprese PV 01790620189
R.E.A. PV. 221363

210 **ACTIV**

SUPER-CTIVE POLISHING DETERGENT

Technical information

Self-polishing concentrated detergent for quick washing of cars, trucks, portable containers, canvases, buses, motors, machines, ships, garbage cans etc. Once sprayed, it develops a strong super-active penetrating power and, after taking off and suspending the dirt, it becomes easy to rinse. The perfectly balanced mixture of surface active agents, combined with special polishers, ensures the cleanliness and makes the washed surface shine, even when working at different temperatures. The careful selection of raw materials has granted a highly-biodegradable product, in accordance with the current regulations against pollution. It can be highly diluted, even with hard water, and breaks quickly down the electrostatic bond between atmospheric dirt and the car's body, allowing a perfect cleansing, even by fast washing systems. **No need to sponge or brush.**

CHEMICAL COMPOSITION: Non ionic surface active agents, alkalizing agents, adjuvants, polishing agents, suspending agents, dirt-emulsifying agents, water.

PH: ph 11,5

DIRECTIONS FOR USE:

WITH SPRAY: Dilute with water (1:50-100), spray it uniformly on the whole surface from the bottom up to the top and rinse cold using high pressure. As for all detergents, it is advisable to cool off hot dark-painted surfaces with water before applying the product and prevent the drying. Do not spray the concentrated product on aluminium and its alloys

WITH SELF-AREA HIGH-PRESSURE CLEANER: Dilute the product with water (1:200-300), apply it on the whole car from a distance of 15 cm and then rinse thoroughly. It is recommended to work at 50-60° C.

WITH HIGH-PRESSURE: Avoid the drying of the product on painted surfaces. Do not spray the concentrated product on aluminium and its alloys.

PACKAGE: kg. 12–25-60 kg. canisters / 220 kg. drums